

### Future-proof your processes

Want your team to work faster without compromising on quality? You don't need to create yet another 'time management' training course. There's a much smarter way to boost productivity in the 2020s. Introducing the IM C530FB and IM C530F — the high-speed, compact, all-in-one line of devices that do all of the heavy 'lifting' for you, as quick as a flash. This means your team can focus on the areas and tasks that enable them to get their work done...instead of having to wait for that 87-page report to get printed without a paper jam...

Our new A4 colour devices are specifically designed to boost your team's productivity efficiently and effectively. IM C530FB (base model) and IM C530F (finisher model) optimize digital workflows with apps and solutions available in the cloud. As a result, all of your processes can work seamlessly, without costly interruptions or waiting times.

- · Work faster: Seamlessly print up to 53 pages per minute, cut waiting times and boost productivity.
- Optimize digital workflows: Share and instantly use all types of information, thanks to the MFP cloud connection.
- Scale up at your own pace: Easily customize, manage and add new features to your device, using the new 7" touchscreen control panel.
- Save space: IM C530FB and IM C530F are compact devices designed to take up less space and leave more room for your pressing needs.
- Seamlessly print documents: Print up to 3,250 sheets without interruption and make light work of printing tasks.
- Save time: With IM C530F you work more efficiently by automating manual tasks, such as separating or stapling files together, thanks to the standard finishing function.
- Intuitive and fast operation: The 7" smart operation panel provides consistent operability across multiple devices in our portfolio. Simply follow the steps on screen.

Think of all of the things you can do in a matter of seconds on your smartphone. Now imagine what your team could achieve with IM C530FB and IM C530F, the high-speed all-in-one printers designed to significantly optimize your workflows and scale up productivity.

# Optimize your workflows and boost productivity with minimum hassle

#### High speed A4 colour printing

The IM C530FB and IM C530F, with its standard finishing function, have the capacity to seamlessly print up to 53 pages per minute and deliver up to 3,250 pages without compromising quality, thanks to the new large capacity tray. The UI provides consistent operability across multiple devices in our portfolio, so once you manage one device, you can effortlessly use any of them.



#### Fully digitalized workflows = flawless processes

Today's fast-paced working environment dictates that you always stay connected and meet expectations as quickly as possible.

The IM C530FB and IM C530F give you an advantage in this digital era, with easy-to-use workflow apps that connect your printer to your preferred third-party cloud services. What's more, the IM C530FB and IM C530F also restrict access to print output to the document owners only, thanks to the exclusive Streamline NX Secure Release feature. This gives you total control over who gets access to documents, whether they're members of your team or clients.

# Future-proof technology to spearhead your business growth

There's no need to keep updating your devices to get access to new features and functionalities.

With our Always Current Technology, you'll instantly receive the latest updates and always stay one step ahead. IM C530FB and IM C530F allow new software features, applications and upgrades to be downloaded and installed directly to your device on request. This way, the everchanging needs of your business are promptly met. You'll never have to sit and wait for new functionalities to keep up with your business plans. Now you can easily future-proof your company's growth.



# Product configuration

## Mainframe IM C530F IM C530FB Internal Finisher SR1020 (for IM C530F only) Stack capacity: 500 sheets Staple capacity: 50 sheets Dimensions: 450.8 × 477.6 × 248 mm Weight: 7 kg 7" Smart Operation Panel 100-sheet SPDF 550-sheet input tray 150-sheet bypass tray 500-sheet output tray Weight: 42 kg Dimensions: 470 x 502.8x 843.7 mm 7" Smart Operation Panel 100-sheet SPDF 550-sheet input tray 150-sheet bypass tray 400 sheet output tray Weight: 28 kg Dimensions 470 x 502.8 x 643.7 mm Minimum space requirements Front: 514 mm Left: 100 mm Reght: 350 mm Regr: 305 mm Top: 234 mm Paper Feed Unit PB1180 LCT PB1190 Capacity: 2,000 sheets Dimensions: 724.2 x 772.1 x 459 mm Weight: 32.4 kg Capacity: 550 sheets Dimensions: 420 x 464.5 x 123 mm Weight: 6.5 kg

#### Other options

- FIFE 802.11 Interface Unit Type M43

  NI C Card Reader Type M43

  Unitode Fort Package for SAP 1 Licence

  Unitode Fort Package for SAP 10 Licence

  Counter Interface Type M12

  Medium Cabinet 76

  Llow Capinet 75

  Caster Table 74

Dimensions are stated in width x depth x height (W x D x H)



### **IM C530FB/IM C530F**

MAIN SPECIFICATIONS

	IM C530FB	IM C530F
GENERAL		
Configuration	Desktop	
Printing process	Dry –two component electro-	photographic printing
Development	Non magnetism, single component development	
Technology	Electro photographic printing system with laser beam	
Warm-up time	39 seconds	
First copy speed: B/W	4 seconds	
First copy speed: full colour	4.2 seconds	
Continuous output speed	53 ppm	
Memory: standard	2 GB	
Memory: maximum	2 GB	
Storage	eMMC: 32GB	
SPDF capacity	100 sheets	
Duty cycle	150.000	
	,	
Duplex	Yes	40 1:
Weight Dimensions: W x D x H	38 kg 470 x 502.8 x 643.7 mm	42 kg 470 x 502.8 x 843.7 mm
Power source	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz
	220 240 4, 00 00 112	220 240 V, 00 00 112
COPIER		
First copy speed	BW: 6.5 seconds, Colo	ur: 6.6 seconds
Multiple copying	Up to 999 co	ppies
Resolution	1,200 x 1,20	0 dpi
Colour mode setting	Default: Black and	white mode
	Auto Colour Selec	` ,
	Full color	
	Black and w	
	Single color	
Reproduction ratio	400%, 200%, 155%, 141%, 129%, 122%, 121%, 115%, 100%, 9	
Maximum original size	Book: A3, DL	•
7	ADF: A3, DL	
Zoom	From 25% to 400%	•
Paper selection	1st tray 2nd tray	
	3rd tray (with par	
	4th tray (with pap	
	Bypass tra	
	LCT	
PRINTER		
CPU	ARM CortexA53 - Dua	al core1 2 GHz
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulat	
Print resolution: maximum	1,200 x 1,20	
Print resolution	PCL5c: 300 dpi	•
Till Tooluloi	PCL6: 600 dpi, 1.200	•
	PS3: 600 dpi, 1.200	• • • •
Interface	Standard: Mainframe (Ethernet (1000BASE-T/100BASE-TX/10BASE	
	4.2, SD card slot (1Slot/Support SDHC memory card), USB host (Ty	/pe A:1Port/Support USB flash memory), Optional USB host
	(TypeA:1Port/Support keyboard), Optional USB host (Type Mini B	
	expansion of ROM storage of the operation unit, Wireless LAN (IEEE	
	Forum Type2 Tag	
Mark the materials and 1999	Option: Wireless LAN (IE	• ,
Mobile printing capability	Apple AirPrint, Mopria®, Google Cloud Pri	
Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 20 Windows® Server	
		0. 20.0
Mac OS environments	Macintosh 8.6 or later	(OS X Classic)
Mac OS environments	Macintosh 8.6 or later ( Macintosh OS X v1	· · · · · · · · · · · · · · · · · · ·
Mac OS environments  UNIX environments		0.12 or later
	Macintosh OS X v1	0.12 or later ver (5.0.7, 6.0), RedHat® Linux Enterprise (4, 5, 6), IBM® AIX
	Macintosh OS X v1 UNIX Sun® Solaris (9), HP-UX (11.x, 11i v2, 11i v3), SCO OpenServ	0.12 or later ver (5.0.7, 6.0), RedHat® Linux Enterprise (4, 5, 6), IBM® AIX nApp (7.15 or Later)
UNIX environments	Macintosh OS X v1 UNIX Sun® Solaris (9), HP-UX (11.x, 11i v2, 11i v3), SCO OpenServ (V6.1, V7.1, V7.2), Citrix Xei SAP® R/3®, SAI PCL5c: Windows 7 (32/64bit), Windows 8.1 (32/64bit), Windows 1	0.12 or later ver (5.0.7, 6.0), RedHat® Linux Enterprise (4, 5, 6), IBM® AIX nApp (7.15 or Later) P® S/4® 0 (32/64bit), Server 2008 (32/64bit), Server 2008R2 (64bit),
UNIX environments  SAP® environments	Macintosh OS X v1  UNIX Sun® Solaris (9), HP-UX (11.x, 11i v2, 11i v3), SCO OpenServ (V6.1, V7.1, V7.2), Citrix Xer  SAP® R/3®, SAI  PCL5c: Windows 7 (32/64bit), Windows 8.1 (32/64bit), Windows 1  Server 2012/R2 (64bit), Server 2016, SAP R/3, SAP S/4, Unix Sun	0.12 or later ver (5.0.7, 6.0), RedHat® Linux Enterprise (4, 5, 6), IBM® AIX nApp (7.15 or Later) P® S/4® 0 (32/64bit), Server 2008 (32/64bit), Server 2008R2 (64bit), Solaris, HP-UX, SCO OpenServer, Red Hat Linux, IBM AIX
UNIX environments  SAP® environments	Macintosh OS X v1 UNIX Sun® Solaris (9), HP-UX (11.x, 11i v2, 11i v3), SCO OpenServ (V6.1, V7.1, V7.2), Citrix Xer SAP® R/3®, SAI PCL5c: Windows 7 (32/64bit), Windows 8.1 (32/64bit), Windows 11 Server 2012/R2 (64bit), Server 2016, SAP R/3, SAP S/4, Unix Sun PCL6: Windows 7 (32/64bit), Server 2008 (32/64bit), Server 2008	0.12 or later  or (5.0.7, 6.0), RedHat® Linux Enterprise (4, 5, 6), IBM® AIX  nApp (7.15 or Later)  p® S/4®  0 (32/64bit), Server 2008 (32/64bit), Server 2008R2 (64bit),  Solaris, HP-UX, SCO OpenServer, Red Hat Linux, IBM AIX  R2 (64bit), Windows 8.1 (32/64bit), Server 2012/R2 (64bit),
UNIX environments  SAP® environments	Macintosh OS X v1  UNIX Sun® Solaris (9), HP-UX (11.x, 11i v2, 11i v3), SCO OpenServ (V6.1, V7.1, V7.2), Citrix Xer  SAP® R/3s, SAI  PCL5c: Windows 7 (32/64bit), Windows 8.1 (32/64bit), Windows 10  Server 2012/R2 (64bit), Server 2016, SAP R/3, SAP S/4, Unix Sun- PCL6: Windows 7 (32/64bit), Server 2008 (32/64bit), Server 2008 (32/64bit), Server 2008	0.12 or later ver (5.0.7, 6.0), RedHat® Linux Enterprise (4, 5, 6), IBM® AIX nApp (7.15 or Later) P® S/4® 0 (32/64bit), Server 2008 (32/64bit), Server 2008R2 (64bit), Solaris, HP-UX, SCO OpenServer, Red Hat Linux, IBM AIX R2 (64bit), Windows 8.1 (32/64bit), Server 2012/R2 (64bit), ), Server 2016
UNIX environments SAP® environments	Macintosh OS X v1 UNIX Sun® Solaris (9), HP-UX (11.x, 11i v2, 11i v3), SCO OpenServ (V6.1, V7.1, V7.2), Citrix Xer SAP® R/3®, SAI PCL5c: Windows 7 (32/64bit), Windows 8.1 (32/64bit), Windows 11 Server 2012/R2 (64bit), Server 2016, SAP R/3, SAP S/4, Unix Sun PCL6: Windows 7 (32/64bit), Server 2008 (32/64bit), Server 2008	0.12 or later ver (5.0.7, 6.0), RedHat® Linux Enterprise (4, 5, 6), IBM® AIX nApp (7.15 or Later) Pv S/4® (0.32/64bit), Server 2008 (32/64bit), Server 2008 (22/64bit), Server 2008R2 (64bit), Solaris, HP-UX, SCO OpenServer, Red Hat Linux, IBM AIX R2 (64bit), Windows 8.1 (32/64bit), Server 2012/R2 (64bit), Server 2016 (64bit), Windows 8.1 (32/64bit), Windows 10 (32/64bit), Server 2016 (64bit), Windows 8.1 (32/64bit), Windows 10 (32/64bit), Server 2016 (32/64bit)

### **IM C530FB/IM C530F**

MAIN SPECIFICATIONS

SCANNER	IM C530FB	IM C530F	
CIS			
Scanning: full colour	46 ipm (simplex)/	52 ipm (duplex)	
Scanning speed: SPDF (A4 LEF,	Simplex: BW (46 ipm (A4, 200dp		
200dpi, B/W full colour)	Duplex: BW (71 ipm (A4, 200dpi		
Resolution: maximum	1,200 dpi	1,200 dpi	
Resolution: standard	Standard: 100 dpi, 200 dpi		
. toodiadon otaniaara	Default: 200 dpi		
Compression method		·	
Compression method BW: TIFF (MH, MR, MMR, JBIG2), Grayscale, Colour: JI File formats Single Page TIFF (Compression on, Compression off), Single page JPEG (Compression on Compression of Single Page TIFF (Compression of S			
THE IOTHALS	Compression off), Single page High compression off), Single page PDF (Compression on), Single page PDF (Compression on), Compression on, Compression off), Multi page PDF (Compression on, Compression off), Multi page PDF (Compression on, Compression off)		
Scan modes	E-mail, Folder, U	JSB. SD Card	
Scan area: main scan	215.9		
Scan area: sub scan			
Network TWAIN	SPDF (405.6 mm), Book OS: Server2008(32bit)/7(32bit)/8.1(32bit)/10(32bit), Server2008(64bit)/7(64bit)/8.1(64bit)/10(64bit)/Server2008R2(64bit)/ Server2012(64bit)/Server2012R2(64bit)/Server2016(64bit)/Server2019(64bit) Resolution: B/W (Book, ARDF)/Colour (Book, ARDF) Scan Mode: Standard/Photo/OCR/Filing Image Adjustment: Brightness/Contrast/Threshold/Gamma Adjustment/Halftone Pattern Endorser: Date/Page Number/Text		
Scan mode (B/W)	BW Text/Line Art, BW Text, BW Tex	t/Photo, BW Photo, BW Gravscale	
Scan mode (colour)	Full Color Text/Photo, Full Color 0	•	
Image density	·	•	
	Automatic/Manual: Yes (		
SADF/batch mode Search method of email address in HDD	Yes Name, E-mail address		
FAX			
Circuit	PSTN,	PBX	
Transmission speed	G3: approximately 3 seconds (200 x 100 dpi, JBI		
•			
Modem speed: maximum	33.6 Kbps		
Resolution: standard	8x3.85 line/mm	•	
	8x7.7 line/mm,	•	
Compression method	MH, MR, MMR		
Scanning speed	46 spm		
Page memory size	Standard: 9.7 MB		
SAF memory size	Standard: 4 MB (approximately 320 pages)		
SID code (sender ID)	Yes		
Programming by OMR	No		
Telephone specifications	Handset/te	elephone	
Total for the specimental of the	Monitor s On hoc Tone trans Pau	speaker ok dial smission	
	Pulse/tone		
	Reception mo Auto answer Busy tone	delay time	
PAPER HANDLING			
Recommended paper size	Standard paper tray(s) (A4, A5, B5, Legal, Letter, Half Letter, Exe	ecutive, Foolscap, Monarch, C5, DL Env), Optional paper tray	
	(A4, A5, B5, Legal, Letter, Half Letter, Executive, Foolscap, C5, E Half Letter, Executive, Foolscap, Monarct	nvelopes), LCT (A4), Bypass tray (A4, A5, A6, B5, Legal, Lett h, C5, C6, DL Env, Custom Size paper)	
Paper input: standard	550 sh		
Paper input: bypass	150 sh	neets	
Paper input: option	Paper bank unit: 550 sheets LCT: 2,000 sheets		
Paper input: maximum	3,250 s		
Paper output: standard	400 sheets	500 sheets	
Paper weight 60 - 220 g/m²	60 - 220 g/m²		
Paper weight Optional tray(s)	60-176 g/m²	60 - 220 g/m²	
Paper weight Optional tray (LCT) Paper weight Bypass	60 - 220 g/m² 60 - 176 g/m²	60-176 g/m² 60 - 220 g/m²	
Paper weight Duplex Paper types	Plain paper, Recycled paper, Special paper 1-3, Letterhead, Enpaper	60 - 176 g/m² velope, Coated paper, Middle thick paper, Thick paper 1, Thic	
A sho a usi a asi a u	pape		
Authentication			
Windows authentication LDAP authentication	Yes, Kerbe	eros (Yes)	

#### **IM C530FB/IM C530F**

MAIN SPECIFICATIONS

IM C530FB IM C530F

Security features

Encryption: Authentication Pwd Encryption, SSL communication, SMTP over SSL/TLS, Transport Layer Security (TLS), Wireless Lan(WEP),

Wireless Lan(WPA), Wireless Lan(11i)

Network Protocol On/Off, IP filtering (Access Control), Mask Type for Copying/Data Security for Copying , Copy Data Security Unit

Option

**ECOLOGY** 

Others:

Power consumption: max.

Power consumption operation:

B&W

Power consumption operation:

Power consumption operation:

Full colour

 Power consumption: ready
 99.8 W

 Power consumption: sleep
 0.75 W

 TEC\*
 0.73 kWh/week

Sound power level: Standby/energy saving (30 dB/30.4 dB), Printing ( dB), Copying (Nominal value)

Sound pressure level: Standby/energy saving (dB), Printing (dB)

Safety regulations

Environmental standard: BAM, Canada Ecologo®

Usage and durability ratings

APV: maximum: 10,000 prints

Duty: 120,000 prints

Estimated life: 5 years or 600,000 output

\* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

#### **OUTPUT TRAYS AND FINISHER OPTIONS**

 4x 550-sheet paper tray
 Paper size: (A4, A5, B5), Paper weight: (60-220 g/m²)

 2,000-sheet Large capacity tray
 Paper size: (A4, LT), Paper weight: (60-176 g/m²)

#### OTHER OPTIONS

Caster table, IEEE 802.11 a/g/n, NFC card reader, Paperlock

#### CONSUMABLES

 
 Starter toner
 Black: 7,500 prints Cyan: 4,500 prints Magenta: 4,500 prints Yellow: 4,500 prints

 Toner (black)
 20,500 prints

 Toner (cyan/magenta/yellow)
 18,000 prints

 Photo conductor/developer unit
 Black: 60,000 sheets Cyan/magenta/yellow: 60,000 sheets

 Fusing unit
 240,000 sheets

 Waste toner bottle
 30,000 sheets

Consumable yield based on 3p/j 5% coverage on A4

**Bluetooth** 







COMMISSION REGULATION (EU) 2019/2020. The light source of this product is not intended for applications other than image printing.

Ricoh Europe (Netherlands) B.V.

"Nieuw Kronenburg" Prof. W.H. Keesomlaan 1 1183 DJ Amstelveen The Netherlands



+31 (0)20 5774111



ricoh-europe.com

